## Amendments to the Claims:

This listing of claims will replace all prior versions, and listings of claims in the application.

## **Listing of Claims:**

checking.

1. (Currently Amended) A method of safeguarding at least one program part that is critical to safety against inadvertent execution, comprising:

executing the at least one program part in a predetermined chronological sequence; at a certain point in time in the execution, generating a pattern <u>using program code</u> that is included in the at least one program part; and

at least at one point in time <u>after the certain point in time when the pattern is generated</u>, checking whether the pattern is present.

- 2. (Original) The method of claim 1, wherein the pattern is generated at a beginning of the execution of the at least one program part.
- 3. (Currently Amended) The method of claim 1, wherein the pattern is generated stored in a volatile memory element.
- 4. (Original) The method of claim 1, further comprising:
  checking an external boundary condition at the time of pattern generation and pattern
- 5. (Original) The method of claim 4, wherein a state of a hardware component serves as the external boundary condition.
- 6. (Currently Amended) A method of safeguarding a program part that is critical to safety, comprising:

performing a check at least at one point in time during an execution of the program part that is critical to safety to determine a presence of a pattern representing a proper sequence of the program part, the pattern being generated using code that is included in the at least one program part; and

terminating the execution of the program part if the pattern is determined to be not present.

7. (Withdrawn) A memory device for storing program instructions to cause a microprocessor to safeguard at least one program part that is critical to safety against inadvertent execution, the microprocessor being divided into at least one area, each area storing a respective one of

the at least one program part, the at least one program part being executable in a predetermined chronological sequence, the memory device comprising:

a first arrangement for generating a pattern at a certain point in time when the at least one program part is executed; and

at least one second arrangement for performing a check at a later point in time to determine whether the pattern is present.

8. (Withdrawn) The memory device of claim 7, further comprising: an arrangement for resetting the microprocessor.